





CLEVIS GRAB HOOK 316 STAINLESS STEEL



ITEM	(size)	A	B	C	D	WLL	WT
						(lb)	(lb)
S0451-0007	1/4"	0.37"	0.41"	0.34"	1.83"	1,500	0.40
S0451-0008	5/16"	0.36"	0.36"	0.40"	2.08"	2,000	0.60
S0451-0010	3/8"	0.47"	0.43"	0.48"	2.55"	2,500	1.05
S0451-0013	1/2"	0.54"	0.50"	0.60"	2.85"	3,600	1.84

NOTE:
WORKING LOADS ARE BASED ON GRADUAL PULL, NOT SHOCK LOADS. INCLUDES REMOVABLE CLEVIS PIN. FOR CHAIN SLING ASSEMBLIES, SEE PAGE 13.


CLEVIS SLIP HOOK 316 STAINLESS STEEL



ITEM	(size)	A	B	C	D	WLL	WT
						(lb)	(lb)
S0452-0007	1/4"	0.37"	0.41"	0.58"	2.57"	1,000	0.57
S0452-0008	5/16"	0.36"	0.40"	0.83"	2.73"	1,500	0.82
S0452-0010	3/8"	0.47"	0.43"	0.95"	3.04"	2,000	1.14
S0452-0013	1/2"	0.54"	0.50"	1.05"	3.53"	3,000	2.13

NOTE:
WORKING LOADS ARE BASED ON GRADUAL PULL, NOT SHOCK LOADS. INCLUDES REMOVABLE LATCH & CLEVIS PIN. FOR CHAIN SLING ASSEMBLIES, SEE PAGE 13. LARGER WLL HOOK DESIGNS ARE IN PROCESS. PLEASE CALL FOR AVAILABILITY.


EYE GRAB HOOK 316 STAINLESS STEEL



ITEM	(size)	A	B	C	D	WLL	WT
						(lb)	(lb)
S0453-0007	1/4"	0.50"	0.35"	2.00"	1,500	0.35	
S0453-0008	5/16"	0.56"	0.43"	2.25"	2,000	0.56	
S0453-0010	3/8"	0.65"	0.50"	2.50"	2,500	0.89	
S0453-0013	1/2"	0.88"	0.66"	3.35"	3,600	1.51	

NOTE:
WORKING LOADS ARE BASED ON GRADUAL PULL, NOT SHOCK LOADS. FOR CHAIN SLING ASSEMBLIES, SEE PAGE 13.

EYE SLIP HOOK 316 STAINLESS STEEL




ITEM	(size)	A	B	C	D	WLL	WT
						(lb)	(lb)
S0454-0007	1/4"	0.53"	0.68"	2.54"	1,000	0.30	
S0454-0008	5/16"	0.65"	0.75"	3.00"	1,500	0.54	
S0454-0010	3/8"	0.71"	0.80"	3.28"	2,000	0.91	
S0454-0013	1/2"	0.94"	1.02"	4.17"	3,000	1.87	

LATCH KIT (REPLACEMENT LATCH, SPRING AND PIN)

Z0454-L007	1/4"						0.01
Z0454-L008	5/16"						0.01
Z0454-L010	3/8"						0.02
Z0454-L013	1/2"						0.04

NOTE:
S0454 HOOKS INCLUDE REMOVABLE LATCH.

SWIVEL EYE HOOK 316 STAINLESS STEEL



ITEM	SIZE	A	B	C	D	WLL	WT
						(lb)	(lb)
S0455-0100	4"	1/4"	0.86"	0.69"	4.64"	770	0.40
S0455-0120	5"	5/16"	1.09"	0.75"	5.50"	1,430	0.70
S0455-0150	6"	3/8"	1.10"	0.75"	6.29"	2,200	1.15
S0455-0200	8"	1/2"	1.41"	1.15"	7.78"	3,300	2.30

LATCH KIT (REPLACEMENT LATCH, SPRING AND PIN)

Z0455-L100	4"						0.01
Z0455-L120	5"						0.02
Z0455-L150	6"						0.02
Z0455-L200	8"						0.03


NOTE:
LIGHT DUTY SWIVEL HOOK. HEAVY DUTY IS S0457 SERIES ON NEXT PAGE. WORKING LOADS ARE BASED ON GRADUAL PULL, NOT SHOCK LOADS. INCLUDES REMOVABLE LATCH. STAMPED WITH SIZE AND WORKING LOAD.





SWIVEL EYE HOOK

316-NM STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0457-0140	1.24"	0.84"	5.58"	0.40"	1,000	0.88
S0457-0170	1.47"	0.88"	6.52"	0.53"	1,500	1.44
S0457-0180	1.70"	0.94"	7.65"	0.65"	2,000	2.28
S0457-0210	1.69"	1.07"	8.12"	0.64"	2,500	2.60

NOTE:
HEAVY DUTY SWIVEL HOOK WITH DROP FORGED COMPONENTS.
LOAD RATED FOR OVERHEAD LIFTING. INCLUDES REMOVABLE SAFETY LATCH.

SHANK HOOK

316-NM STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0456-0100	1/2"	0.84"	5.06"	2.00"	1,000	0.66
S0456-0120	5/8"	0.88"	5.53"	2.25"	1,500	0.90
S0456-0150	3/4"	0.94"	6.25"	2.50"	2,000	1.34
S0456-0200	7/8"	1.07"	6.90"	2.75"	2,500	1.86

NOTE:
LOAD RATED. HEAVY DUTY SHANK HOOK.
INCLUDES REMOVABLE SAFETY LATCH.
CUSTOM THREADS AVAILABLE IN UNF, UNC AND METRIC.

THREADED SHANK HOOK

316-NM STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(thread size)				(lb)	(lb)
S0458-0100	1/2" - 13	0.84"	5.06"	2.00"	1,000	0.66
S0458-0120	5/8" - 11	0.88"	5.53"	2.25"	1,500	0.90
S0458-0150	3/4" - 10	0.94"	6.25"	2.50"	2,000	1.34
S0458-0200	7/8" - 9	1.07"	6.90"	2.75"	2,500	1.86

NOTE:
LOAD RATED. HEAVY DUTY SHANK HOOK.
INCLUDES REMOVABLE SAFETY LATCH.
STANDARD UNC THREADS.

EYE HOOK

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0194-0001	3/4"	0.66"	3.90"	1.88"	300	0.27
S0194-0002	1-1/8"	0.77"	4.62"	2.10"	350	0.39

NOTE:
WORKING LOADS ARE BASED ON GRADUAL PULL, NOT SHOCK LOADS. INCLUDES REMOVABLE SAFETY LATCH.

WIDE ASYMMETRICAL CLIP

316 STAINLESS STEEL



ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
S0195-0100	3/8"	0.74"	4.00"	400	0.30
S0195-0120	7/16"	1.00"	4.75"	540	0.43

NOTE:
ALSO AVAILABLE WITH EYE ON SPECIAL ORDER.
BULK ORDERS OF OTHER SIZES MAY BE PLACED ON SPECIAL ORDER.



Key:



Made in USA



Drop Forged



Precision Machined



Wire Formed



Suncor Exclusive



Import



Precision Cast



Stamped



Load Rated



New Product


ORDERS ONLY: 800-394-2222 (USA)
877-495-5510 (CANADA)

All logos, icons, images, measurements and descriptions are the sole property of Suncor Stainless, Inc.

© 2002 Suncor Stainless, Inc.




ASYMMETRICAL SPRING CLIP 316 STAINLESS STEEL



ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
S0140-0080	3"	0.60"	0.31"	700	0.16
S0140-0100	4"	0.75"	0.40"	1,350	0.31

NOTE:
EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILOWEIGHTS.
CONVERSION: KN X 224.8 = LB.
BREAK LOAD IS APPROXIMATELY 4 TIMES THE WORK LOAD LIMIT.


SPRING CLIP (WIRE LEVER) 316 STAINLESS STEEL



ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
S0141-0080	3"	0.62"	0.31"	700	0.15
S0141-0100	4"	0.75"	0.40"	1,350	0.29

NOTE:
FEATURES LONG LASTING TORSION SPRING GATE.
EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILOGRAMS.
CONVERSION: KG X 2.2 = LB.


SCREW LOCK SPRING CLIP 316 STAINLESS STEEL



ITEM	A	B	C	D	E	WLL	WT
	(size)	(ID)				(lb)	(lb)
S0181-0060	1/4"	0.25"	2.38"	0.31"	0.23"	250	0.07
S0181-0080	5/16"	0.40"	3.13"	0.27"	0.37"	400	0.16
S0181-0100	3/8"	0.48"	4.00"	0.45"	0.46"	600	0.30
S0181-0120	7/16"	0.61"	4.63"	0.59"	0.55"	800	0.44
S0181-0140	15/32"	0.83"	5.55"	0.83"	0.63"	1,000	0.61

NOTE:
SCREW LOCK NUT PREVENTS ACCIDENTAL OPENING.
EYELET IS REMOVABLE. COMMERCIAL GRADE.

KEY LOCK SPRING CLIP 316 STAINLESS STEEL




ITEM	A	B	C	D	E	WLL	WT
	(size)	(ID)				(lb)	(lb)
S0181-K100	3/8"	0.44"	4.00"	0.51"	0.42"	800	0.32
S0181-K120	7/16"	0.59"	5.00"	0.61"	0.57"	1,000	0.46

NOTE:
WITH KEY LOCK MECHANISM. SCREW LOCK NUT PREVENTS ACCIDENTAL OPENING. EYELET IS REMOVABLE.

EACH CLIP IS PROOF TESTED AND STAMPED WITH BREAK LOAD IN KILOGRAMS.

CONVERSION: KGX2.2=LB.

SPRING CLIP 316 STAINLESS STEEL



ITEM	A	B	C	D	E	WLL	WT
	(size)	(ID)				(lb)	(lb)
S0120-0050	3/16"	0.32"	2.00"	0.25"	0.24"	120	0.04
S0120-0060	1/4"	0.36"	2.38"	0.27"	0.27"	170	0.06
S0120-0070	9/32"	0.45"	2.75"	0.34"	0.37"	200	0.10
S0120-0080	5/16"	0.48"	3.13"	0.38"	0.37"	280	0.15
S0120-0100	3/8"	0.63"	3.88"	0.54"	0.47"	400	0.28
S0120-0120	7/16"	0.75"	4.63"	0.65"	0.55"	540	0.41
S0120-0140	15/32"	0.87"	5.50"	0.80"	0.60"	740	0.58
S0120-0160	1/2"	1.03"	6.25"	0.95"	0.79"	900	0.79


NOTE:
EACH CLIP IS STAMPED WITH "316" AND WLL (LB).
COMMERCIAL GRADE.





SPRING CLIP (KEY LOCK)

316 STAINLESS STEEL




ITEM	A	B	C	D	E	WLL	WT
	(size)	(ID)				(lb)	(lb)
S0120-K050	3/16"	0.31"	2.00"	0.29"	0.20"	200	0.04
S0120-K060	1/4"	0.35"	2.38"	0.37"	0.21"	250	0.07
S0120-K070	9/32"	0.46"	2.88"	0.40"	0.33"	300	0.10
S0120-K080	5/16"	0.44"	3.25"	0.43"	0.33"	400	0.16
S0120-K100	3/8"	0.55"	4.00"	0.60"	0.40"	600	0.30
S0120-K120	7/16"	0.69"	4.75"	0.70"	0.57"	800	0.43
S0120-K160	1/2"	0.87"	6.38"	1.18"	0.75"	1,000	0.78

NOTE:
KEY LOCK MECHANISM. EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILOGRAMS.
CONVERSION: KGX2.2=LB.

SPRING CLIP WITH EYE

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)	(ID)			(lb)	(lb)
S0121-0050	3/16"	0.25"	2.00"	0.25"	120	0.04
S0121-0060	1/4"	0.30"	2.38"	0.27"	150	0.06
S0121-0070	9/32"	0.32"	2.75"	0.34"	200	0.10
S0121-0080	5/16"	0.40"	3.13"	0.38"	280	0.15
S0121-0100	3/8"	0.50"	3.88"	0.54"	400	0.28
S0121-0120	7/16"	0.60"	4.71"	0.65"	500	0.41
S0121-0140	15/32"	0.80"	5.50"	0.80"	750	0.58
S0121-0160	1/2"	0.87"	6.25"	0.95"	900	0.79

NOTE:
EACH CLIP IS STAMPED WITH "316" AND WLL (LB).
COMMERCIAL GRADE.

SPRING CLIP with EYE (KEY LOCK)

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)	(ID)			(lb)	(lb)
S0121-K050	3/16"	0.24"	2.00"	0.29"	200	0.04
S0121-K060	1/4"	0.27"	2.38"	0.37"	250	0.07
S0121-K070	9/32"	0.35"	2.88"	0.40"	300	0.10
S0121-K080	5/16"	0.39"	3.25"	0.43"	400	0.16
S0121-K100	3/8"	0.45"	4.00"	0.66"	600	0.30
S0121-K120	7/16"	0.59"	4.75"	0.70"	800	0.43
S0121-K160	1/2"	0.87"	6.38"	1.18"	1,000	0.78

NOTE:
KEY LOCK MECHANISM. EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILOGRAMS.
CONVERSION: KGX2.2=LB.

SPRING CLIP (SPECIAL GATE)

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)	(ID)			(lb)	(lb)
WITHOUT EYELET:						
S0142-0080	5/16"	0.45"	3.25"	0.54"	500	0.16
S0142-0100	3/8"	0.56"	4.00"	0.62"	700	0.30
S0142-0120	7/16"	0.70"	4.75"	0.85"	1,000	0.43
WITH EYELET:						
S0143-0080	5/16"	0.39"	3.25"	0.54"	500	0.16
S0143-0100	3/8"	0.45"	4.00"	0.62"	700	0.30
S0143-0120	7/16"	0.58"	4.75"	0.85"	1,000	0.43

NOTE:
EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILOGRAMS.
CONVERSION: KG X 2.2 = LB.

MOORING HOOK OR KIT

316 STAINLESS STEEL



ITEM	TYPE	WT
		(lb)
C0182-K120	5" S0172-S120 CLIP WITH HOLDER ON A DISPLAY CARD	0.62
S0182-0000	MOORING HOOK HOLDER ONLY	0.09

NOTE:
THIS HOLDER WILL ALLOW THE SPRING CLIP TO STAY OPEN IN ORDER TO ATTACH LINE TO MOORING.
SPECS ON S0172-S120 ARE LISTED ON PAGE 49.



Key:

Made in USA	Drop Forged	Precision Machined	Wire Formed	Suncor Exclusive
Import	Precision Cast	Stamped	Load Rated	New Product


ORDERS ONLY: 800-394-2222 (USA)
877-495-5510 (CANADA)

All logos, icons, images, measurements and descriptions are the sole property of Suncor Stainless, Inc. © 2002 Suncor Stainless, Inc.



HARNES CLIP (WIRE LEVER)

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)	(ID)			(lb)	(lb)
S0184-0060	1/4"	0.32"	2.38"	0.38"	260	0.06
S0184-0080	5/16"	0.52"	3.25"	0.56"	650	0.15
S0184-0100	3/8"	0.66"	4.00"	0.58"	1,000	0.30
S0184-0120	1/2"	0.86"	5.00"	0.81"	1,500	0.62

NOTE:
FORGED END. STAMPED WITH WORKING LOAD (LB). BREAKING LOAD IS 5 TIMES THE WORK LOAD SHOWN.
FEATURES LONG LASTING TORSION SPRING GATE.



HARNES CLIP (WIRE LEVER)

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)	(ID)			(lb)	(lb)
S0172-0060	1/4"	0.31"	2.38"	0.43"	260	0.07
S0172-0080	5/16"	0.52"	3.25"	0.62"	750	0.16
S0172-0100	3/8"	0.67"	4.00"	0.69"	1,200	0.30
S0172-0120	1/2"	0.85"	5.00"	0.90"	2,000	0.52

STRAIGHT BACK VERSION
NOTE:
FORGED END. STAMPED WITH WORKING LOAD.
FEATURES LONG LASTING TORSION SPRING GATE.



HARNES CLIP (POLY GRIP)

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0184-N100	4"	0.66"	0.58"	0.39"	1,000	0.31
S0184-N120	4-3/4"	0.86"	0.81"	0.50"	1,500	0.64

NOTE:
FORGED END. STAMPED WITH WORKING LOAD. (LB.) BREAKING LOAD IS 5 TIMES THE WORK LOAD SHOWN. FEATURES LONG LASTING TORSION SPRING GATE.
POLYURETHANE GRIPS ALLOW FOR SUPERIOR HANDLING. IN SAFETY ORANGE.



HARNES CLIP WITH D RING

304 STAINLESS STEEL



ITEM	A	B	C	D	E	WLL	WT
	(size)					(lb)	(lb)
S0223-8025	3-1/4"	0.52"	0.56"	0.31"	1.00"	650	0.20


NOTE:
"D" RING IS FORGED.

SEE RATCHET BUCKLES AND OUR LINE OF WEBBING/TIE-DOWN HARDWARE STARTING ON PAGE 81.



KEY RING

304 STAINLESS STEEL



ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
S0185-KR01	0.08"	1.00"	0.15"	NOT RATED	0.01
S0185-KR02	0.05"	0.50"	0.08"	NOT RATED	0.01
S0185-KR03	0.07"	0.75"	0.12"	NOT RATED	0.01

NOTE:
304 STAINLESS STEEL WITH NICKEL PLATING.
MINIMUM PURCHASE OF 100.




TEL 508-732-9191 • FAX 508-732-9798 • ORDERS ONLY 800-394-2222

5 02-896-5656 www.osc.co.kr



SPRING CLIP WITH KEY RING



316 STAINLESS STEEL



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0185-KR60	2-3/8"	1.00"	0.38"	0.23"	NOT RATED	0.07


NOTE:
THE ENDS OF THE CLIP ARE FORGED.
THE 1 INCH KEY RING IS FORMED FROM STAINLESS, THEN NICKEL PLATED FOR SUPERIOR FINISH.

POP DISPLAY HOLDS 100 CLIPS:
C0185-KR60BX

USA DESIGN KEY CLIP


ALUMINUM



ITEM	A	B	C	WLL	WT	
	(size)			(lb)	(lb)	
S0186-US80	1"	3.15"	0.50"	0.32"	NOT RATED	0.05


NOTE:
LIGHTWEIGHT ALUMINUM WITH HIGH IMPACT GRAPHICS OF THE AMERICAN FLAG.

POP DISPLAY HOLDS 100 CLIPS:
C0186-US80BX




MINI CLIP (WIRE LEVER)

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0185-0035	1-3/8"	0.23"	0.20"	0.16"	65	0.02

NOTE:
USE ANYWHERE A SMALL CLIP IS NEEDED. USE FOR CAMERAS, FLASHLIGHTS AND MORE. WIRE LEVER IS DURABLE FOR YEARS OF RELIABILITY. HIGHLY POLISHED FINISH. THE SMALLEST HIGH QUALITY STAINLESS CLIP AVAILABLE.



SPRING GATE SNAP


316 STAINLESS STEEL



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0161-0050	2"	0.38"	0.40"	0.25"	150	0.05
S0161-0070	2-3/4"	0.42"	0.61"	0.39"	350	0.13
S0161-0100	3-3/4"	0.55"	0.87"	0.59"	500	0.32

TRIGGER SNAP "D" BAIL

316 STAINLESS STEEL



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0192-0001	5/8"	2.43"	0.23"	0.43"	200	0.12
S0192-0002	3/4"	2.50"	0.23"	0.43"	200	0.12
S0192-0003	1"	2.65"	0.22"	0.43"	200	0.13



Key:



Made in USA



Drop Forged



Precision Machined



Wire Formed



Suncor Exclusive



Import



Precision Cast



Stamped



Load Rated



New Product


ORDERS ONLY: 800-394-2222 (USA)
877-495-5510 (CANADA)

All logos, icons, images, measurements and descriptions are the sole property of Suncor Stainless, Inc. © 2002 Suncor Stainless, Inc.



TRIGGER SNAP EYE BAIL


316 STAINLESS STEEL



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0193-0001	1/2"	2.62"	0.15"	0.43"	200	0.11
S0193-0002	5/8"	2.65"	0.20"	0.43"	200	0.11

SWIVEL EYE SNAP


316 STAINLESS STEEL



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0174-0001	5/8"	3.37"	0.20"	0.40"	100	0.14
S0174-0002	3/4"	3.87"	0.24"	0.47"	200	0.22
S0174-0003	7/8"	4.62"	0.27"	0.51"	300	0.35

FIXED EYE SNAP


316 STAINLESS STEEL



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0175-0000	7/16"	2.10"	0.15"	0.22"	100	0.05
S0175-0001	5/8"	2.71"	0.19"	0.37"	200	0.10
S0175-0002	3/4"	3.12"	0.20"	0.50"	250	0.13
S0175-0003	3/4"	3.75"	0.28"	0.60"	300	0.24

SWIVEL BOLT SNAP


316 STAINLESS STEEL



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0176-0000	3/8"	2.73"	0.32"	0.28"	100	0.06
S0176-0001	1/2"	3.16"	0.36"	0.37"	200	0.09
S0176-0002	5/8"	3.44"	0.43"	0.36"	250	0.11
S0176-0003	3/4"	3.60"	0.43"	0.36"	300	0.12
S0176-0004	1-1/4"	4.63"	0.48"	0.53"	350	0.20

DOUBLE BOLT SNAP

316 STAINLESS STEEL



ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
S0176-0900	3-1/2"	0.25"	0.33"	100	0.09
S0176-1000	4"	0.37"	0.43"	200	0.15
S0176-1200	4-3/4"	0.48"	0.47"	250	0.19


NOTE:
ALLOWS EASY CONNECTION AND DISCONNECTION AT EITHER END.





U.S. NAVY BOLT SNAP

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0177-USN6	6-1/2"	0.63"	0.93"	0.72"	1,000	1.06

NOTE:
BUREAU OF SHIPS NUMBER: S8101A1,464,418
PRODUCT IS USUALLY ATTACHED TO CHAIN WITH OPEN END, WHICH IS THEN BENT CLOSED.

FIXED SNAP SHACKLE

316 STAINLESS STEEL




ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
S0158-0001	2"	0.42"	0.56"	1,000	0.10
S0158-0002	2-5/8"	0.51"	0.75"	1,500	0.21
S0158-0003	3-3/4"	0.68"	1.10"	2,000	0.49

NOTE:
BREAKLOAD IS APPROXIMATELY 4 TIMES THE WORK LOAD LIMIT.

JAW SWIVEL SNAP SHACKLE

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0170-0001	2-3/4"	0.57"	0.54"	0.24"	800	0.14
S0170-0002	3-1/2"	0.75"	0.60"	0.27"	1,200	0.27
S0170-0003	5"	1.05"	0.87"	0.48"	1,800	0.88

NOTE:
STAMPED BAIL. REMOVABLE JAW PIN.
BREAKLOAD IS APPROXIMATELY 4 TIMES THE WORK LOAD LIMIT.

JAW SWIVEL SNAP SHACKLE

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0171-0001	2-3/4"	0.57"	0.54"	0.23"	1,000	0.17
S0171-0002	3-1/2"	0.75"	0.52"	0.31"	1,500	0.36
S0171-0003	5"	1.05"	0.75"	0.48"	2,000	0.95

NOTE:
REMOVABLE CLEVIS PIN.
BREAKLOAD IS APPROXIMATELY 4 TIMES THE WORK LOAD LIMIT.

SWIVEL SNAP SHACKLE

316 STAINLESS STEEL



ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
S0157-0001	2-3/4"	0.50"	0.57"	1,000	0.13
S0157-0002	3-1/2"	0.62"	0.75"	1,500	0.28
S0157-0003	4-3/4"	0.85"	1.05"	2,000	0.67

NOTE:
BREAKLOAD IS APPROXIMATELY 4 TIMES THE WORK LOAD LIMIT.



Key:

Made in USA	Drop Forged	Precision Machined	Wire Formed	Suncor Exclusive
Import	Precision Cast	Stamped	Load Rated	New Product


ORDERS ONLY: 800-394-2222 (USA)
 877-495-5510 (CANADA)

All logos, icons, images, measurements and descriptions are the sole property of Suncor Stainless, Inc. © 2002 Suncor Stainless, Inc.



JIB HANK


BRONZE



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
B0169-0000	1-1/2"	0.23"	0.40"	0.25"	75	0.05
B0169-0001	2-1/4"	0.50"	0.83"	0.43"	100	0.10
B0169-0002	2-1/2"	0.63"	0.90"	0.43"	125	0.15
B0169-0003	3"	0.67"	0.97"	0.43"	135	0.20

SWIVEL EYE SNAP

304 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0166-0003	3/4"	0.31"	2.87"	0.16"	130	0.07

NOTE:
SEE RATCHET BUCKLES AND OUR LINE OF WEBBING/TIE-DOWN HARDWARE BEGINNING ON PAGE 81.


CHAIN SWIVEL SNAP

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0645-0005	5/32 - 3/16"	0.21	0.32	2.87	130	0.07

NOTE:
STANDARD OR LONG LINK CHAIN, UP TO 3/16" (WIRE) SIZE, CAN BE ATTACHED TO CLIP. USE CLIP AT THE END OF TWIST LINK CHAIN FOR A DOG LEASH OR AT THE END OF A KILL CORD FOR WATERCRAFTS.

SWIVEL WEB CLIP

304 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0221-0025	1"	0.63"	0.32"	2.56"	130	0.07
S0221-0038	1-1/2"	0.63"	0.32"	2.63"	130	0.08
S0221-0050	2"	0.63"	0.32"	2.71"	130	0.10

NOTE:
NEW "SLIMLINE" BAIL FOR WEBBING; SPECIAL TORSION SPRING GATE FOR LONGER LIFE. IDEAL FOR BIMINI TOPS AND HOLD DOWN STRAPS. SEE RATCHET BUCKLES AND OUR LINE OF WEBBING/TIE-DOWN HARDWARE STARTING ON PAGE 81.

FIXED BIMINI CLIP

304 STAINLESS STEEL



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0220-0025	1"	0.23"	0.20"	1.94"	70	0.03


NOTE:
IDEAL FOR BIMINI TOPS AND HOLD DOWN STRAPS. SEE RATCHET BUCKLES AND OUR LINE OF WEBBING/TIE-DOWN HARDWARE STARTING ON PAGE 81.





PELICAN HOOK WITH SLIDE

316 STAINLESS STEEL




ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
S0180-0100	4"	0.39"	0.75"	200	0.22
S0180-0150	6"	0.51"	0.97"	300	0.56

NOTE:
PELICAN HOOK # S0162 IS FEATURED ON PAGE 28.

HOG RING AND SHOCKCORD


304 STAINLESS STEEL



ITEM	A	B	C	WT
	(size)			(lb)
HOG RINGS:				
S0183-0005	3/16"	0.38"	0.08"	0.19/100
S0183-0007	1/4"	0.51"	0.08"	0.20/100
S0183-0008	5/16"	0.62"	0.08"	0.21/100
S0183-0010	3/8"	0.74"	0.08"	0.23/100
S0183-0013	1/2"	0.87"	0.08"	0.24/100
SHOCK CORD ENDS:				
S0183-SC05	3/16"	0.62"	1.50"	0.02
S0183-SC07	1/4"	0.62"	1.50"	0.03
S0183-SC08	5/16"	0.88"	1.77"	0.04
S0183-SC10	3/8"	0.94"	1.84"	0.05
S0183-SC13	1/2"	1.14"	2.68"	0.06

DOWNHAUL HOOK

316 STAINLESS STEEL




ITEM	A	B	C	D	WT
	(size)				(lb)
S0179-H008	5/16"	0.50"	2.47"	1.40"	0.12
S0179-H010	3/8"	0.50"	3.50"	2.05"	0.25

NOTE:
CAN BE USED IN SAILING APPLICATIONS OR AS CARGO LASHING HOOK.

REEFING HOOK

316 STAINLESS STEEL




ITEM	A	B	C	D	WT
	(size)				(lb)
S0179-R008	5/16"	0.24"	3.50"	1.30"	0.16
S0179-R010	3/8"	0.24"	4.15"	1.84"	0.31

NOTE:
ATTACHMENT END IS FORGED FLAT FOR EASY INSTALLATION.

TACK HOOK

316 STAINLESS STEEL



ITEM	A	B	C	D	WT
	(size)				(lb)
S0179-T008	5/16"	0.24"	3.12"	1.48"	0.10
S0179-T010	3/8"	0.24"	3.56"	1.90"	0.18

NOTE:
CAN BE USED IN SAILING APPLICATIONS OR AS CARGO LASHING HOOK. ATTACHMENT END IS FORGED FLAT FOR EASY INSTALLATION.



Key:



Made in USA



Drop Forged



Precision Machined



Wire Formed



Suncor Exclusive



Import



Precision Cast



Stamped



Load Rated



New Product


ORDERS ONLY: 800-394-2222 (USA)
877-495-5510 (CANADA)

All logos, icons, images, measurements and descriptions are the sole property of Suncor Stainless, Inc. © 2002 Suncor Stainless, Inc.



CUNNINGHAM HOOK


316 STAINLESS STEEL



ITEM	A	B	C	D	WT
	(size)				(lb)
S0179-CH07	1/4"	0.42"	2.45"	1.72"	0.07
S0179-CH08	5/16"	0.62"	3.80"	2.42"	0.19

DOUBLE "J" WEB HOOK

304 STAINLESS STEEL




ITEM	SIZE	A	B	C	WLL	WT
					(lb)	(lb)
S0211-0025	1"	0.78"	0.27"	2.77"	400	0.15
S0211-0038	1-1/2"	0.78"	0.38"	3.44"	1,500	0.40
S0211-0050	2"	0.78"	0.38"	3.44"	1,500	0.41

NOTE:
SEE RATCHET BUCKLES AND OUR LINE OF WEBBING/TIE-DOWN HARDWARE STARTING ON PAGE 81.

WELDED "S" WEB HOOK

316 STAINLESS STEEL




ITEM	SIZE	A	B	C	D	WLL	WT
						(lb)	(lb)
S0212-0025	1"	0.25"	4.00"	1.00"	1.00"	200	0.12
S0212-0038	1-1/2"	0.31"	4.50"	1.50"	1.50"	300	0.22
S0212-0050	2"	0.38"	6.18"	2.25"	2.00"	400	0.46

NOTE:
QUALITY "S" HOOK IS WELDED TO PREVENT WEBBING FROM SLIPPING THROUGH. BULK ORDERS OF OTHER SIZES OR TYPES MAY BE PLACED ON SPECIAL ORDER.
FOR ANCHOR AND PAD EYES, SEE PAGES 90 TO 95.

"S" HOOK

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0178-0003	1/8"	1.38"	0.20"	0.42"	50	0.01
S0178-0004	5/32"	1.59"	0.20"	0.51"	80	0.02
S0178-0005	3/16"	1.90"	0.29"	0.63"	120	0.04
S0178-0006	1/4"	2.25"	0.32"	0.70"	200	0.06
S0178-0008	5/16"	2.58"	0.46"	0.75"	350	0.12

NOTE:
BULK ORDERS OF OTHER SIZES OR TYPES MAY BE PLACED ON SPECIAL ORDER.

"U" HOOK

316 STAINLESS STEEL




ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0179-0006	1/4"	2.15"	0.42"	0.35"	300	0.06
S0179-0008	5/16"	2.95"	0.65"	0.62"	400	0.14
S0179-0010	3/8"	3.35"	0.75"	0.67"	500	0.26





HARNES CLIP - AUTO LOCK


W/ HD FIBERGLASS LOCK



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
ALUMINUM						
A0146-0012	7/16"	0.70"	4.91"	0.84"	1,600	0.18
316 STAINLESS STEEL						
S0146-0012	7/16"	0.70"	4.91"	0.84"	2,000	0.46
ZINC-PLATED CARBON STEEL						
Z0146-0012	7/16"	0.70"	4.91"	0.84"	1,600	0.46
NOTE: EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILONEWTONS. CONVERSION: KN X 224.8 = LB. BREAK LOAD IS APPROXIMATELY 3 TIMES THE WORK LOAD LIMIT.						

XL CLIP - AUTO LOCK


W/ HD FIBERGLASS LOCK



ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
ALUMINUM					
A0147-0013	1/2"	1.06"	4.50"	2,200	0.20
316 STAINLESS STEEL					
S0147-0013	1/2"	1.06"	4.50"	2,500	0.50
ZINC-PLATED CARBON STEEL					
Z0147-0013	1/2"	1.06"	4.50"	3,500	0.50
NOTE: EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILONEWTONS. CONVERSION: KN X 224.8 = LB. BREAK LOAD IS APPROXIMATELY 3 TIMES THE WORK LOAD LIMIT.					

HARNES CLIP - SCREW LOCK


ALUMINUM W/ ALUMINUM LOCK



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
A0148-0008	5/16"	0.47"	3.40"	0.66"	400	0.06
A0148-0010	3/8"	0.52"	4.06"	0.67"	1,200	0.12
A0148-0012	7/16"	0.70"	4.92"	0.91"	1,600	0.18
NOTE: EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILONEWTONS. CONVERSION: KN X 224.8 = LB. BREAK LOAD IS APPROXIMATELY 3 TIMES THE WORK LOAD LIMIT.						

HARNES CLIP - SCREW LOCK


316 STAINLESS STEEL W/ STAINLESS LOCK



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
S0148-0008	5/16"	0.47"	3.40"	0.66"	1,000	0.18
S0148-0010	3/8"	0.52"	4.06"	0.67"	1,500	0.34
S0148-0012	7/16"	0.70"	4.92"	0.91"	2,000	0.50
NOTE: EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILONEWTONS. CONVERSION: KN X 224.8 = LB. BREAK LOAD IS APPROXIMATELY 3 TIMES THE WORK LOAD LIMIT.						

HARNES CLIP - SCREW LOCK

ZINC-PLATED CARBON STEEL W/ BRASS LOCK



ITEM	A	B	C	D	WLL	WT
	(size)				(lb)	(lb)
Z0148-0008	5/16"	0.47"	3.40"	0.66"	600	0.18
Z0148-0010	3/8"	0.52"	4.06"	0.67"	1,200	0.34
Z0148-0012	7/16"	0.70"	4.92"	0.91"	1,600	0.50
NOTE: EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILONEWTONS. CONVERSION: KN X 224.8 = LB. BREAK LOAD IS APPROXIMATELY 3 TIMES THE WORK LOAD LIMIT.						



Key:




ORDERS ONLY: 800-394-2222 (USA)
877-495-5510 (CANADA)

All logos, icons, images, measurements and descriptions are the sole property of Suncor Stainless, Inc. © 2002 Suncor Stainless, Inc.



XL CLIP - SCREW LOCK

ALUMINUM W/
ALUMINUM LOCK




ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
A0149-0013	1/2"	1.06"	4.50"	2,200	0.20

NOTE:
EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILONEWTONS.
CONVERSION: KN X 224.8 = LB.
BREAK LOAD IS APPROXIMATELY 3 TIMES THE WORK LOAD LIMIT.

XL CLIP - SCREW LOCK

316 STAINLESS STEEL
W/ STAINLESS LOCK




ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
S0149-0013	1/2"	1.06"	4.50"	2,500	0.56

NOTE:
EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILONEWTONS.
CONVERSION: KN X 224.8 = LB.
BREAK LOAD IS APPROXIMATELY 3 TIMES THE WORK LOAD LIMIT.

XL CLIP - SCREW LOCK

ZINC-PLATED CARBON STEEL
W/ BRASS LOCK




ITEM	A	B	C	WLL	WT
	(size)			(lb)	(lb)
Z0149-0013	1/2"	1.06"	4.50"	3,500	0.56

NOTE:
EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILONEWTONS.
CONVERSION: KN X 224.8 = LB.
BREAK LOAD IS APPROXIMATELY 3 TIMES THE WORK LOAD LIMIT.

EXT CLIP - SLIDE LOCK

316 STAINLESS STEEL
W/ STAINLESS LOCK




ITEM	A	B	C	D	E	WLL	WT
	(size)					(lb)	(lb)
S0145-0008	5/16"	0.46"	3.16"	0.99"	0.40"	600	0.16
S0145-0010	3/8"	0.59"	3.95"	1.29"	0.44"	900	0.31

NOTE:
EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD IN KILONEWTONS.
CONVERSION: KN X 224.8 = LB.
BREAK LOAD IS APPROXIMATELY 3 TIMES THE WORK LOAD LIMIT.

ROPE SNAP SHACKLE

316 STAINLESS STEEL



ITEM	A	B	C	WT
	(size)			(lb)
S0159-0001	2"	0.55"	0.42"	0.12
S0159-0002	2-5/8"	0.68"	0.57"	0.22
S0159-0003	3-3/4"	1.05"	0.88"	0.70

